

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

## 1 Identification

- **Trade name:** Pall-X Power
- **Application of the substance / the mixture** Waterborne 1-component hardwood floor finish
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Manufacturer:  
 PALLMANN GmbH  
 Im Kreuz 6  
 D-97076 Würzburg  
 Germany  
 Phone +49 931-27964-0  
 Fax +49 931-27964-50
- **Supplier:**  
 Uzin Utz North America, Inc.  
 14509 E. 33rd. Place, Unit G  
 Aurora, CO 80011  
 Phone: +720-374-4810  
 Toll-Free: +1 866-505-4810  
 Fax: +1 720-374-2113
- **Information department:**  
 Products Development Lab  
 E-Mail: [msds.info@uzin-utz.com](mailto:msds.info@uzin-utz.com)
- **Emergency telephone number:**  
 For Chemical Emergency Spill Leak Fire Exposure or Accident  
 Call CHEMTREC Day or Night: DOMESTIC NORTH AMERICA 800-424-9300  
 International, call +49 621 60 43 333

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
 The product is not classified, according to the Globally Harmonized System (GHS).
- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**  
 NFPA Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.  
 NFPA is the National Fire Protection Association.  
 HMIS Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.  
 HMIS®, the Hazardous Materials Identification System, is a registered mark of the National Paint and Coatings Association (NPCA).
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

Trade name: **Pall-X Power**

(Contd. of page 1)

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Waterborne 1-component hardwood floor finish

- **Hazardous ingredients:**

CAS: 34590-94-8	Dipropylene glycol monomethyl ether Flam. Liq. 4, H227	3-<5%
CAS: 5131-66-8	3-butoxypropan-2-ol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	1-<3%

- **Additional information:**

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.  
For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Call a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub> extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

(Contd. on page 3)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

Trade name: **Pall-X Power**

(Contd. of page 2)

### · Protective Action Criteria for Chemicals

#### · PAC-1:

CAS: 34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
-----------------	-------------------------------------	---------

#### · PAC-2:

CAS: 34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
-----------------	-------------------------------------	-----------

#### · PAC-3:

CAS: 34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
-----------------	-------------------------------------	------------

## 7 Handling and storage

### · Handling:

#### · Precautions for safe handling

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

#### · Storage:

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Protect from frost.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### **CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

<i>PEL</i>	Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
------------	--

<i>REL</i>	Short-term value: 900 mg/m <sup>3</sup> , 150 ppm Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
------------	---

<i>TLV</i>	Short-term value: 909 mg/m <sup>3</sup> , 150 ppm Long-term value: 606 mg/m <sup>3</sup> , 100 ppm Skin
------------	---

### · Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· **Respiratory protection:** Not required.

(Contd. on page 4)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

Trade name: **Pall-X Power**

(Contd. of page 3)

### · Protection of hands:



PVC or PE gloves

· **Material of gloves** PVC or PE gloves

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Fluid
· <b>Color:</b>	Whitish
· <b>Odor:</b>	Weak, characteristic

· **pH-value at 20 °C (68 °F):** 7.7

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

· **Boiling point/Boiling range:** Undetermined.

· **Flash point:** > 100 °C (>212 °F)

· **Ignition temperature:** > 200 °C (>392 °F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Density at 20 °C (68 °F):** 1.04 g/cm<sup>3</sup> (8.68 lbs/gal)

· **Solubility in / Miscibility with**

· **Water:** Fully miscible.

· **Viscosity:**

· **Kinematic at 20 °C (68 °F):** 20 s (DIN 53211/4)

· **Other information** No further relevant information available.

## 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

Trade name: **Pall-X Power**

(Contd. of page 4)

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Specific symptoms in biological assay:**
- **Primary route(s) of entry:** Inhalation, skin contact, eye contact, ingestion.
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritant effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**  
None of the ingredients is listed.
- **NTP (National Toxicology Program)**  
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**  
None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Do not allow product to reach sewage system.  
Absorb smaller quantities with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust), allow to harden, then dispose of as construction waste.  
Dispose of bigger amounts in accordance with Local Authority requirements.
- **Uncleaned packagings:**
- **Recommendation:**  
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

-US

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

Trade name: **Pall-X Power**

(Contd. of page 5)

## 14 Transport information

· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	-
· DOT, ADR, ADN, IMDG, IATA	Void
· DOT, ADN, IMDG, IATA	
· Class	Void
· DOT, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport/Additional information:	Not regulated as hazardous material according to the above specifications.
· UN "Model Regulation":	Void

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)

· **EPCRA Section 302 (Extremely Hazardous Substances):**

None of the ingredient is listed.

· **SARA Title III Section 313 (Toxic Release Inventory - TRI):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

US

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/16/2019

Version No. 2

Reviewed on 01/16/2019

**Trade name: Pall-X Power**

(Contd. of page 6)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Contact:**

Mr. Adam Vernati, phone +1 720-420-4685  
mobile +1 307-314-8312

· **Date of preparation / last revision 01/16/2019 / 1**

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· **\* Data compared to the previous version altered.**

US